



Bose Electro Acoustics

Amplifiers



Hi-Fi 6 Channel Tuner Audio Amplifier AV-455E

With USB + SD/MMC card Reader. Full function remote control VFD Display

Inputs: 2(AC-3 - 5.1 channel Analog Inputs, VCD) + USB/SD/MMC Card reader + Built-in AM/FM Receiver.

Outputs: Front Left, Front Right, Surround Left, Surround right & Centre - all 30 Watt RMS,

Subwoofer - 80 Watt RMS with Cross Over Frequency Control. 2 ports Available to Connect Active Subwoofer Amplifier

Frequency Response: 20Hz-20KHz

Distortion: $\leq 0.5\%$ **Input impedance :** 47k

Input Sensitivity : $\leq 300\text{mV}$

Dimensions: 430(W) x 380mm(D) x 65mm(H)



Hi-Fi Stereo Tuner Amplifier A-777

Inputs: 4(TV, CD, DVD, IPOD) + Built-in USB + SD/MMC Card Reader + Digital AM/FM Receiver, 2 Microphone Inputs For Karaoke with Digital Delay & Echo

Outputs: Speaker Outputs A + B (Left + Right Channels) Line Out, REC Out, Pre-Amp Out & Power Amp Input, Headphone Out

Specifications:

Power Output: 150 Watt RMS/Channels

Total Harmonic Distortion: $\leq 0.5\%$

Input Impedance: 47K

Input sensitivity: $\leq 300\text{ mV}$

Treble Adjustment: $\pm 15\text{dB}$

Mid-range Adjustment: $\pm 7\text{dB}$

Bass Adjustment: $\pm 15\text{dB}$

Loudness: 100Hz - +8dB, 10KHz - +3 dB

Mic. Treble and Bass Adjustment: $\pm 10\text{dB}$

Frequency Response: 20Hz - 20KHz ($\pm 1\text{ dB}$)

Microphone Input Sensitivity: $\leq 20\text{mV}$

Dimensions: (W) 430mm x (D) 380mm x (H) 110mm



Bose Electro Acoustics



SA-2010

Inputs: 2 (CD, Tape)

Outputs: Main Speakers + Surround Speakers

Specifications: Power Outputs Per Channel RMS @ 8 ohms - 10W

Frequency Response: 20Hz to 20,000 Hz

Distortion: Less than 0.1%

Tone Controls: Bass @ 50Hz +/- 15db Treble @ 10Khz +/- 15db

Loudness: + 6db @50 Hz and + 5db @ 10Khz

Dimensions: 280mm(W) x 60mm(W) x 220mm(D)



Hi-Fi Stereo Tuner Audio Amplifier AV-455C

Full function remote control VFD Display

Input: 5 (VCD, Tape, CD, DVD, TV) + Built-in AM/FM Receiver & 2 Microphone Inputs for Karaoke with Digital Delay & Echo.

Outputs: Speaker Outputs (Left + Right Channels) - 100 Watt RMS Per Channel @ 8 ohms, record Output & Line Output

Frequency Response: 20Hz - 20KHz

Distortion: $\leq 0.5\%$

Input Sensitivity: $\leq 300\text{mV}$

Dimensions: 430mm(W) x 320mm(D) x 65mm(H).



Hi-Fi Stereo Tuner Audio Amplifier AV-2020

Full function remote control VFD Display

Inputs: 3 (VCD, Tape, DVD) + Built-in AM/FM Receiver

Outputs: Speaker Outputs(Left + right channels) - 20 Watt RMS Per Channel @ 8 ohms

line Output Available to Connect an Active Subwoofer if required.

Frequency Response: 20Hz - 20KHz

Distortion: $\leq 0.5\%$

Dimensions: 430mm(W) x 320mm(D) x 50mm(H).



Bose Electro Acoustics

Speakers



TOWER SPEAKERS MERCURY

Power Handling: 120 Watt

Impedance: 8 Ohms

Sensitivity: 1W/1M) - 87dB

Frequency Response: 40Hz- 200000Hz

Driver Configuration: 1" Silk Dome Tweeter - 1 No.

5.25" Midrange - 1 No.

10" Woofer - 1 No.

Features: 2 x 5.25" High Power Woofers and 1 Silk Dome Tweeter.

Dimensions: 970mm(H) x 193mm(W) x 375mm(D).



CEILING SPEAKER

6" Speaker - Co-Axial

Power of speaker: 15 Watt RMS

Impedance: 8 Ohms

fitted with LMT having taps at 6 W, 3 W, 1.5 W

Dimensions: 9.25"

Dog ears for smooth mounting in the ceiling

Speakers Chasis: Metal



Double Cube Satellite Speaker

Driver Configuration: 2 x 3" Hi Performance Driver

Maximum Input Power: 30 Watt RMS Per Satellite



Bose Electro Acoustics



Single Cube Satellite Speaker

Driver Configuration: 1 x 3" Hi Performance Driver
Maximum Input Power: 30 Watt RMS Per Satellite
Can be used with Amplifier AV 455B.



2 MINI SPEAKER PB-101

Mini 2 way Speakers in a luxurious piano black finish
Components: 3" Woofer & 1" Silk Dome Tweeter with 12dB/Octave cross over
Power Handling-35 Watt RMS & if fitted with Hi-pass filter (Available on request) can handle up to 70 Watt RMS
Frequency Response: 200 Hz - 20Khz
Dimensions: Height 180mm Depth 148mm
Depth with wall mounting stand 208mm
Width Front - 105mm width center - 120mm
Width Rear - 70mm



PASSIVE SUBWOOFER

Power Handling: 50W RMS Per Channel
Ideal System for a home Theatre Using 5 Double Cube satellites
Sub-Woofer: 8 Ohms
Features: 2 x 5.25" High Power Woofers
Dimensions: 200mm(L) x 470mm(D) x 365mm(H)



Bose Electro Acoustics



ACTIVE SUBWOOFER DS-120

Power Output: 150 Watt RMS

Phase switch

Volume Control

12" High Power woofer

Variable Crossover Frequency Control

High & Low level Input & Output

High Power Toroidal Transformer

Dimensions: (W)415mm x (D)520mm x (H)460mm



SPEAKER SYSTEM FOR LCD TV LS-3000R

Specifications

Clean Stylish Design to Match The LCD TV (32"-42")

2.0 Channel Speaker System

30 Watt RMS Total Output Power

Wooden cabinet For Clean Deep Bass & Excellent High Frequency Response

Stereo Driver: 3" Woofer x 2 + 1.5" Tweeter x 2

Frequency Response: 100-18000Hz

Dimensions: (W)930mm x (D)130mm x (H)135mm

Audio Card Readers



USB + SD / MMC Audio card Reader

Now there is no need to buy expensive 5 CD changers for your background music installation applications. Just dump all your favourite music into a USB Pen drive or SD / MMC Card. Dock the Pen Drive/card into the card reader and you can playback the music through the amplifiers connected to the line out of the card reader.

The unit also has aux in for connecting an IPOD/CD Player. We can also provide a separate version for the car.